Promethean UST-P1 Projector

THIS DOCUMENT CONTAINS SPECIFICATIONS FOR

Promethean UST Projector

DESCRIPTION

The Promethean UST-P1 Projector is a high-performance Ultra-Short Throw DLP unit for classroom use with Promethean's range of ActivBoards and stands.

OVERVIEW

Installation	The installation of this product should be completed by a Promethean Certified Installer. Please visit www.PrometheanWorld.com/ActivCare/installationtc. Use of components not supplied by Promethean or not meeting minimum specifications may impact performance and affect warranty. Contact your Promethean partner or visit www.prometheankb.com for more information.
Warranty	For Promethean Warranty Terms and Conditions please visit: www.PrometheanWorld.com/ActivCare
Support	Online Support for all Promethean Products available from: www.PrometheanKB.com

GENERAL SPECIFICATIONS

		Specifications
Native Resolution		WXGA (1280 x 800)
Aspect Ratio		Native 16:10, 4:3, 16:9, Fill, Letterbox
Throw Ratio		0.35 (Throw distance 77" at 1m)
Contrast Ratio		3000:1
Brightness	(High)	3000 ANSI lumens
	(Normal)	2500 ANSI lumens
Lamp Life	(Normal)	5000 hours
	(Eco)	8000 hours
Power Use	(High)	300W
	(Standby)	< 0.5W excluding RJ45
Acoustic Noise	(High)	33dB (220W)
	(Normal)	29dB (190W)
Inputs		VGA (D-sub 15 RGB) x 2, Composite Video (RCA) x 1, HDMI v1.4a x 1, Audio In (3.5mm) x 1, Audio Out (3.5mm) x 1
Control		USB x 1, RJ45 x1, RS232 x 1
Languages		22 On Screen Display: Arabic, Chinese (Simplified and Traditional), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Projector Weight and Dimensions		3.7kg (8.2lb); 374mm x 287mm x 110mm (14.7" x 11.3" x 4.3")
Packed Weight and Dimensions		9.0kg (19.9lb); 519mm x 440mm x 291mm (20.4" x 17.3" x 11.5")
Promethean System Compatibility		All sizes of ActivBoards; V4 Mount, Fixed, Adjustable stands

www.PrometheanWorld.com