



## 27" IPS monitor with WQHD resolution perfect for multi-monitor set-ups

With an attractive 3-side borderless design the ProLite XU2793QS is perfect for multi-monitor setups. The IPS panel and WQHD (2560x1440) resolution, offers noticeably sharper images, excellent colour performance, wide viewing angles, making this ideal for productivity solutions, demanding office, and financial applications. Featuring a 1ms response time and FreeSync, this is suitable for the home office environment and casual gaming.

Equipped with speakers, headphone socket, HDMI and DisplayPort connections, a blue light reducer function to reduce eye fatigue and compatibility with iiyama desktop arm accessories for multiscreen productivity solutions, make this 27" XU2793QS display is ideal for any modern workplace.

Available also with height adjustable stand: [ProLite XUB2793QS-B1](#)



### IPS Technology

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.



### WQHD

With true WQHD 2560 x 1440p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen, i.e. over 76% more in comparison to a 1920 x 1080 monitor.

## 01 DISPLAY CHARACTERISTICS

|                      |   |
|----------------------|---|
| Design               | 3-side borderless   |
| Diagonal             | 27", 68.5cm   |
| Panel                | IPS panel technology LED, matte finish                                |
| Native resolution    | 2560 x 1440 @75Hz (DisplayPort&HDMI, 3.7megapixel WQHD)               |
| Aspect ratio         | 16:9  |
| Panel brightness     | 300 cd/m <sup>2</sup>   |
| Static contrast      | 1000:1  |
| Advanced contrast    | 80M:1   |
| Response time (MPRT) | 1ms   |
| Viewing zone         | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support       | 1.07B 10bit (8bit + Hi-FRC) (sRGB: 96%; NTSC: 72%)                    |
| Horizontal Sync      | 30 - 120kHz   |
| Viewable area W x H  | 596.7 x 335.7mm, 23.5 x 13.2"   |
| Pixel pitch          | 0.233mm   |
| Colour               | matte, black  |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                     |                           |
|---------------------|---------------------------|
| Signal input        | HDMI x2<br>DisplayPort x1 |
| HDCP                | yes                       |
| Headphone connector | yes                       |

## 03 FEATURES

|                    |   |
|--------------------|---|
| Blue light reducer | yes   |
| Flicker free       | yes   |
| FreeSync support   | yes   |
| Extra              | i-style Colour  |
| OSD languages      | EN, DE, FR, IT, RU, JP, CZ, NL, PL  |
| Control buttons    | Power, Menu, + / Volume, - / Eco, Input Select/ Exit  |
| User controls      | picture (brightness, contrast, black tuner, sharpness, overdrive, ACR, Eco, X-res technology, MBR), colour (warm, normal, cool, user colour, i-Style colour, gamma), input select, audio (volume, mute), language, OSD settings (OSD H. position, OSD V. position, OSD background, OSD time out, information), setup menu (video mode adjust, HDMI RGB range, blue light reducer, DDC/CI, Adaptive Sync, opening logo, LED) |
| Speakers           | 2 x 2W  |
| Convenience        | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX   |

## 04 MECHANICAL

|                              |                 |
|------------------------------|-----------------|
| Display position adjustments | tilt            |
| Tilt angle                   | 20° up; 4° down |
| VESA mounting                | 100 x 100mm     |
| Cable management system      | yes             |

## 05 ACCESSORIES INCLUDED

|        |                                 |
|--------|---------------------------------|
| Cables | power, HDMI                     |
| Other  | quick start guide, safety guide |

## 06 POWER MANAGEMENT

|                   |   |
|-------------------|---|
| Power supply unit | internal                                  |
| Power supply      | AC 100 - 240V, 50/60Hz                    |
| Power usage       | 25W typical, 0.5W stand by, 0.5W off mode |

## 07 SUSTAINABILITY

|   |  |
|---|--|
| Regulations   | CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| Energy efficiency class (Regulation (EU) 2017/1369) | F  |
| REACH SVHC  | above 0.1%: Lead   |

## 08 DIMENSIONS / WEIGHT

|                              |                     |
|------------------------------|---------------------|
| Product dimensions W x H x D | 612.5 x 481 x 236mm |
| Box dimensions W x H x D     | 685 x 435 x 145mm   |
| Weight (without box)         | 4.7kg               |
| Weight (with box)            | 6kg                 |
| EAN code                     | 4948570118953       |



